

WMK-2372

Desktop Network Security Appliance



Front view



Rear view

Features

- Intel® Celeron® N3350 Processor SoC
- Onboard LPDDR4, 1GB, Optional DDR3L 1866MHz Single-Channel SODIMM x 1 (Max 8GB, up to 1600MHz)
- 10/100/1000Base-TX x 4
- Onboard 8GB eMMC, SATA 6.0 Gb/s Port x 1
- Mini-Card Slot (with SIM Socket) x 1
- RJ45 Console x 1, USB 3.2 Gen 1 x 2



Specifications

System

Form Factor	Desktop Network Appliance
Processor	Intel® Celeron® N3350 Processor
Memory	Onboard LPDDR4, 1GB, Optional DDR3L 1866MHz Single-Channel SODIMM x 1 (Max 8GB, up to 1600MHz)
Chipset	Intel® Celeron® N3350 Processor
Storage	Onboard LPDDR4, 1GB, Optional DDR3L 1866MHz Single-Channel SODIMM x 1 (Max 8GB, up to 1600MHz)
CF/CFast/mSATA	Onboard 8GB eMMC SATA 6.0 Gb/s port x 1, for SATA DOM
Mini-PCIe Slot	Mini-Card socket (full-size) with SIM socket x 1
USB	USB 3.2 Gen 1 x 2
RTC	Internal RTC
Watchdog Timer	1~255 steps by software programmable
TPM	(TPM v1.2 9660/TPM2.0 9665 Optional)
Fan	Fanless
MTBF (hours)	162,469
Color	Silver
Mechanical/ Environmental	
Power Requirement	12V DC Power in connector

Storage Temperature	-4°F ~ 140°F (-20°C ~ 60°C)
Operating Temperature	32°F ~ 104°F (0°C ~ 40°C)
Humidity	10%~80% @40°C; non-condensing
Operating Humidity	10%~80% relative humidity, non-condensing
Vibration	0.5 Grms/ 5 ~ 500Hz / operation (SATA DOM) 1.5 Grms/ 5 ~ 500Hz / non operation
Shock	10 G peak acceleration (11 m sec. duration), operation 20 G peak acceleration (11 m sec. duration), non operation
Dimensions	6.1" x 3.62" x 1.26" (155mm x 92mm x 32mm)

I/O Front Panel	Power LED x 1 Status LED x 1 Storage Activ x 1 LAN LED x 8
Rear Panel	USB 3.2 Gen 1 Port x 2 RJ-45 Port x 4 RJ-45 Console x 1 12V DC Power Input x 1 Software Reset Button x 1 Power Button x 1 Antenna Hole x 2

Ordering Information

Standard

PART NUMBER	FWS-2272E4-A10-A10-01
CPU	Intel® Celeron® N3350
MEMORY	Onboard 1GB LPDDR4
BYPASS	-
MINI-CARD SLOT	Full Full Size (USB Only)+ SIM socket x 1
STORAGE	Onboard 8GB eMMC, SATA 6.0 Gb/s Port x 1
LAN	Intel® Ethernet Controller I210, GbE x 4
USB	USB 3.2 Gen 1 x 2
CONSOLE	RJ-45 x 1
SYSTEM FAN	Fanless
MOUNTING	Desktop
POWER	DC
DISPLAY	-

Optional

1700091805	Console Cable
1702021836	Power Cord, 2P/2P, 1.8M, EU

* Specifications and certifications may vary based on different requirements.

Packing List

1 x DC power adapter 12V/5A or
12V/7A 1 x Power cord- US

1 x SATA cable

Optional Accessories

Part Number	Description
1700091805	Console Cable
1702021832	Power Cord, 2P/2P, 1.8M, USA
1702021836	Power Cord, 2P/2P, 1.8M, EU

Dimensions



